

Air Filtration Service Parts from DeVilbiss® Automotive Refinishing

Air Filtration Unit	Order No.	Service Part	Service Part Description	Replacement Interval
 DeVilbiss® DAD-PRO	130538		First stage removes oil, water and dirt down to 5 microns.	Clean as needed, replace only when necessary.
	130539		Second stage removes oil vapors and dirt particulates down to .01 microns.	Replace every 6 months.
	130504		Quick change desiccant bag removes water vapor from compressed air down to a dew point of -40°F.	Indicator provided Green=OK, Yellow=replace
 Camair® CT30	130504		Quick change desiccant bag removes water vapor from compressed air down to a dew point of -40°F.	Indicator provided Green=OK, Yellow=replace
 Camair® CT-Plus™	130517		First stage removes water and dirt to 40 microns.	Replace every 3 months.
	130518		Second stage removes oil and vapors to .01 microns.	 (check with air flowing)
	130504		Quick change desiccant bag removes water vapor from compressed air down to a dew point of -40°F.	Indicator provided Green=OK, Yellow=replace
	130534		CT Plus Tune Up Kit contains: 130504 desiccant cartridge, 130517 water filter element, 130518 coalescing filter element and humidity indicator.	Indicator provided Green=OK, Yellow=replace
 Camair® 130523	130517		First stage removes water and dirt to 40 microns.	Replace every 3 months.
	130518		Second stage removes oil and vapors to .01 microns.	 (check with air flowing)
 Camair® 130526	130517		First stage removes water and dirt to 40 microns.	Replace every 3 months.
	130518		Second stage removes oil and vapors to .01 microns.	 (check with air flowing)
	130527		Third stage removes oil vapor and odors.	Replace every 6 weeks.
 Camair® 130525	130524		Removes water, oil and dirt to 0.1 microns. Kit contains replacement cartridge, O-rings and humidity indicator.	Indicator provided Blue=Ok, White=replace
 Camair® TS-10	130507		Second stage removes oil and vapors to .01 microns.	Replace every 3 months
	130508		Complete Tune Up Kit for TS-10 includes 10 lbs desiccant, coalescing filter and humidity indicator.	Indicator provided Green=OK, Yellow=replace
 DeVilbiss® 130041 & 130042	HAF-6		Removes water and dirt to 5 microns.	Replace every 3 months
 DeVilbiss® HAF-518	HAF-6		Removes water and dirt to 5 microns.	Replace every 3 months
	HAF-28		Removes oil and vapors to .01 microns.	Indicator provided Green=OK, Red=replace (check with air flowing)
 DeVilbiss® DAD-500	HAF-6		First stage removes water and dirt to 5 microns.	Replace every 3 months
	HAF-28		Second stage removes oil and vapors to .01 microns.	Indicator provided Green=OK, Red=replace (check with air flowing)
	DAD-1		Third stage 10 lb. desiccant refill removes humidity from the air.	Indicator provided Blue=OK, Pink/White=replace
	DAD-600		Tune Up Kit for DAD-500 includes 10 lbs desiccant and filter element.	See above for filter change outs
	DAD-600-1		Complete Tune Up Kit for DAD-500 includes 10 lbs desiccant, filter element and coalescing filter element.	See above for filter change outs
 FinishLine® HAR-602 & Sharpe® 606	HAF-39		Removes water and dirt to 5 microns.	Replace every 3 months.
 FinishLine® HAF-580 & HAR-680	HAF-47		Removes water and dirt to 5 microns.	Replace every 3 months.
 Sharpe® 6760	DAD-1		Third stage removes humidity from the air. 10 lbs Desiccant refill for two 5-lbs changes of Sharpe 6760. Replaces Sharpe 6765-1.	Indicator provided Blue=OK, Pink/White=replace (place indicator paper into sight glass)